

3-WAY POWER DIVIDER

CONNECTORIZED MODEL: DCK-7J2S

WIDE BANDWIDTH

1 - 500 MHz


FEATURES:

- ▶ Excellent Performance
- ▶ Wide Bandwidth
- ▶ Small Size
- ▶ Moderate Power
- ▶ Applications: Signal Splitting & Low Power Combining



SPECIFICATIONS (Rev. A 09/28/06)

Frequency	1 - 500 MHz		
Insertion Loss	Freq. (MHz)	dB (Typ.)	dB (Max.)
	1-5	0.4	0.75
	5-250	0.5	0.9
Isolation	Freq. (MHz)	dB (Typ.)	dB (Min.)
	1-5	30	20
	5-250	30	20
Phase Unbalance	Freq. (MHz)	Degrees (Max.)	
	1-5	2	
	5-250	3	
Amplitude Unbalance	Freq. (MHz)	dB (Max.)	
	1-5	0.2	
	5-250	0.3	
Output Impedance	50 Ohms (Nom.)		
	Operating Temperature Range		
			-30 to +85 °C





3-WAY POWER DIVIDER

CONNECTORIZED MODEL: DCK-7J2S

WIDE BANDWIDTH

1 - 500 MHz

PERFORMANCE PLOTS





3-WAY POWER DIVIDER

CONNECTORIZED MODEL: DCK-7J2S

WIDE BANDWIDTH

1 - 500 MHz

PERFORMANCE PLOTS




3-WAY POWER DIVIDER

CONNECTORIZED MODEL: DCK-7J2S

WIDE BANDWIDTH

1 - 500 MHz



PERFORMANCE PLOTS